

**Statement of Basis  
Automotive Coating Operations General Permit**

**Final**



**Taylor Chevrolet Buick & Cadillac  
Rexburg, Idaho  
Facility ID No. 065-00020  
Permit to Construct P-2011.0024  
Project No. 60721**

**January 21, 2011  
Eric Clark  
Permit Writer**

**The purpose of this Statement of Basis is to satisfy the requirements of IDAPA 58.01.01. et seq, Rules for the Control of Air Pollution in Idaho, for issuing air permits.**

<b>ACRONYMS, UNITS, AND CHEMICAL NOMENCLATURE .....</b>	<b>3</b>
<b>FACILITY INFORMATION .....</b>	<b>4</b>
Description .....	4
Permitting History .....	4
Application Scope .....	4
Application Chronology .....	4
<b>TECHNICAL ANALYSIS .....</b>	<b>4</b>
Emissions Units and Control Devices .....	5
Emissions Inventories .....	5
Ambient Air Quality Impact Analyses .....	6
<b>REGULATORY ANALYSIS.....</b>	<b>7</b>
Attainment Designation (40 CFR 81.313) .....	7
Permit to Construct (IDAPA 58.01.01.201).....	7
Tier II Operating Permit (IDAPA 58.01.01.401) .....	8
Visible Emissions (IDAPA 58.01.01.625).....	8
Rules for the Control of Odors (IDAPA 58.01.01.775-776).....	8
Title V Classification (IDAPA 58.01.01.300, 40 CFR Part 70).....	8
PSD Classification (40 CFR 52.21) .....	10
NSPS Applicability (40 CFR 60).....	10
NESHAP Applicability (40 CFR 61).....	10
MACT Applicability (40 CFR 63).....	10
Permit Conditions Review .....	12
<b>PUBLIC REVIEW.....</b>	<b>14</b>
Public Comment Opportunity .....	14
<b>APPENDIX A – EMISSIONS INVENTORIES</b>	

## ACRONYMS, UNITS, AND CHEMICAL NOMENCLATURE

AQCR	Air Quality Control Region
Btu	British thermal units
CAS No.	Chemical Abstracts Service registry number
CE	Control Efficiency
CFR	Code of Federal Regulations
CO	carbon monoxide
DEQ	Department of Environmental Quality
EL	screening emission levels
EPA	U.S. Environmental Protection Agency
gal/day	gallons per calendar day
gal/hr	gallons per hour
gal/yr	gallons per consecutive 12 calendar month period
gr	grain (1 lb = 7,000 grains)
HAP	hazardous air pollutants
HDI	hexamethylene diisocyanate
hr/yr	hours per year
HVLP	high volume, low pressure (applies to paint guns)
IDAPA	a numbering designation for all administrative rules in Idaho promulgated in accordance with the Idaho Administrative Procedures Act
lb/gal	pounds per gallon
lb/hr	pounds per hour
LPG	Liquefied Petroleum Gas
MDI	methylene diisocyanate
MMBtu	million British thermal units
MSDS	Material Safety Data Sheet
NAICS	North American Industry Classification System
NESHAP	National Emission Standards for Hazardous Air Pollutants
NO <sub>2</sub>	nitrogen dioxide
NO <sub>x</sub>	nitrogen oxides
NSPS	New Source Performance Standards
PC	permit condition
PM <sub>10</sub>	particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers
ppm	parts per million
PTC	permit to construct
PTE	potential to emit
Rules	Rules for the Control of Air Pollution in Idaho
scf	standard cubic feet
SIC	Standard Industrial Classification
SM80	synthetic minor facility with emissions greater than or equal to 80% of a major source threshold
SO <sub>2</sub>	sulfur dioxide
SO <sub>x</sub>	sulfur oxides
T/yr	tons per consecutive 12-calendar month period
T2	Tier II operating permit
TAP	toxic air pollutants
TE	Transfer Efficiency
UTM	Universal Transverse Mercator
VOC	volatile organic compounds

## **FACILITY INFORMATION**

### ***Description***

Taylor Chevrolet Buick & Cadillac is an auto body repair and refinishing facility with paint spray booth(s) which is equipped with a paint booth heater. The paint booth(s) is a pressurized downdraft booth(s) with glass fiber filtration media for control of particulate emissions. Drying and paint curing is done in the paint booth(s). The booth(s) is equipped with a natural gas-fired burner to heat the paint booth. The process includes application of coatings via a HVLP (or equivalent) paint gun.

### ***Permitting History***

This is the initial PTC for an existing facility that was constructed in 1994, thus there is no permitting history.

### ***Application Scope***

This is the initial PTC for an existing facility that was constructed in 1994.

### ***Application Chronology***

December 30, 2010	DEQ received an application and an application fee and the processing fee.
January 11 – January 26, 2011	DEQ provided an opportunity to request a public comment period on the application and proposed permitting action.
January 21, 2011	DEQ determined that the application was complete.
January 28, 2011	DEQ made available the draft permit and statement of basis for peer review.
January 11 – January 26, 2011	DEQ provided a public comment period on the proposed action.
February 2, 2011	DEQ issued the final permit and statement of basis.

## **TECHNICAL ANALYSIS**

The facility utilizes glass fiber filtration media for control of particulate matter emissions from the automotive coating operation. In addition, HVLP paint guns (or equivalent) are used to minimize PM<sub>10</sub> and VOC emissions from painting. The HVLP (or equivalent) spray equipment will control PM<sub>10</sub> and VOC emissions by having more paint transfer to the desired surfaces than traditional painting equipment.

## Emissions Units and Control Devices

Table 1 EMISSIONS UNIT AND CONTROL DEVICE INFORMATION

ID No.	Source Description	Control Equipment Description	Emissions Point ID No. and Description
Automotive Coating Operation	<p><b>Paint spray booth(s) and/or preparation station:</b>                      Manufacturer(s): Saico or equivalent                      Model(s): 9411/11V or equivalent                      Note: The number of booths installed at the facility is not limited by this permit.</p> <p><b>Paint booth heater(s):</b>                      Manufacturer(s): Saico or equivalent                      Total Heat input capacity(s): 250,000 Btu/hr (worst-case was assumed to be 10.0 MMBtu/hr)                      Fuel: natural gas only</p>	<p><b>Paint spray booth(s) and/or preparation station filter system:</b>                      Booth Type(s): Down draft                      Particulate filtration method: Dry Filters                      Manufacturer(s): Viledon or equivalent                      Model(s): 200, 300, 400, 500 Series or equivalent                      PM/PM<sub>10</sub> Control Efficiency: 98% or greater</p> <p><b>Coating spray gun(s):</b>                      Manufacturer(s): SATA or equivalent                      Model(s): 2000, 3000 or equivalent                      Type: HVLP or equivalent                      Transfer Efficiency: 65% or greater</p>	Paint booth exhaust stack and/or preparation station exhaust stack

## Emissions Inventories

An emission inventory was developed for the automotive coating operation associated with this proposed project (see Appendix A for a detailed discussion). Emissions estimates of criteria pollutant PTE were based on the worst-case VOC and PM<sub>10</sub> content for coatings as taken from the DEQ Automotive Coating EI spreadsheet (see the DEQ website). Uncontrolled emissions were based upon scaling the annual controlled PTE (based upon the daily coating use limit and typical operation of 2,080 hrs/yr) up to an uncontrolled annual PTE based upon operation of 8,760 hrs/yr.

### Uncontrolled Emissions:

The following table presents the post project uncontrolled emissions for criteria pollutants as submitted by the Applicant and verified by DEQ staff. See Appendix A for a detailed presentation of the calculations and the assumptions used to determine emissions for each emissions unit. Uncontrolled annual emissions were calculated by scaling up the coating operation from normal business annual operations of 2,080 hrs/yr (8 hrs/day x 260 days/yr, normal business hours) to uncontrolled annual operation of 8,760 hrs/yr (24 hrs/day x 365 days/yr).

Table 2 POST PROJECT UNCONTROLLED EMISSIONS FOR CRITERIA POLLUTANTS

Emissions Unit	PM <sub>10</sub>	SO <sub>2</sub>	NO <sub>x</sub>	CO	VOC	Lead
	T/yr	T/yr	T/yr	T/yr	T/yr	lb/quarter
<b>Point Sources</b>						
Paint spray booth(s) and/or preparation station(s)	18.90	0.0	0.0	0.0	59.27	0.0
Paint booth heater(s)	0.32	0.03	4.11	1.75	0.24	0.000022
<b>Total, Point Sources</b>	<b>19.22</b>	<b>0.03</b>	<b>4.11</b>	<b>1.75</b>	<b>59.51</b>	<b>0.00</b>

As demonstrated in Table 2, the facility has an uncontrolled potential to emit for PM<sub>10</sub>, SO<sub>2</sub>, NO<sub>x</sub>, CO, and VOC emissions less than the Major Source threshold of 100 T/yr. Therefore, this facility is not designated as a Synthetic Minor facility. As demonstrated in Table 3 as follows the facility's PTE for all criteria pollutants is less than 80% of the Major Source thresholds of 100 T/yr. Therefore, this facility will not be designated as a SM-80 facility.

This is an existing facility. However, since this is the first time the facility is receiving a permit, pre-project emissions are set to zero for all criteria pollutants.

### Post Project Potential to Emit

The following table presents the post project potential to emit for criteria pollutants from all emissions units at the facility as submitted by the Applicant and verified by DEQ staff. See Appendix A for a detailed presentation of the calculations of these emissions for each emissions unit.

**Table 3 POST PROJECT POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS**

Emissions Unit	PM <sub>10</sub>		SO <sub>2</sub>		NO <sub>x</sub>		CO		VOC		Lead	
	lb/hr <sup>a</sup>	T/yr <sup>b</sup>	lb/hr	T/yr								
<b>Point Sources</b>												
Paint spray booth(s) and/or preparation station(s)	0.03	0.14	0.00	0.00	0.00	0.00	0.00	0.00	4.56	19.98	0	0
Paint booth heater(s)	0.0760	0.079	0.0060	0.006	0.940	0.978	0.400	0.416	0.055	0.057	0.0000050	0.0000052
<b>Post-Project Totals</b>	<b>0.11</b>	<b>0.22</b>	<b>0.01</b>	<b>0.01</b>	<b>0.94</b>	<b>0.98</b>	<b>0.40</b>	<b>0.42</b>	<b>4.62</b>	<b>20.04</b>	<b>0.00</b>	<b>0.00</b>

- a) Controlled average emission rate in pounds per hour is a daily average, based on the proposed daily operating schedule and daily limits.  
b) Controlled average emission rate in tons per year is an annual average, based on the proposed annual operating schedule and annual limits.

As demonstrated in Tables 2 and 3, this facility has an uncontrolled potential to emit for all criteria pollutant emissions less than the Major Source threshold of 100 T/yr and a controlled potential to emit for all criteria pollutant emissions less than the Major Source threshold of 100 T/yr. Therefore, this facility is designated as a Minor facility. As demonstrated in Table 3 the facility's PTE for all criteria pollutants is less than 80% of the Major Source thresholds of 100 T/yr. Therefore, this facility will not be designated as a SM-80 facility.

### Change in Potential to Emit

The change in facility-wide potential to emit is used to determine if a public comment period may be required or if emissions modeling may be required, and to determine the processing fee per IDAPA 58.01.01.225. The following table presents the facility-wide change in the potential to emit for criteria pollutants.

**Table 4 CHANGES IN POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS**

	PM <sub>10</sub>		SO <sub>2</sub>		NO <sub>x</sub>		CO		VOC		Lead	
	lb/hr	T/yr	lb/hr	T/yr	lb/hr	T/yr	lb/hr	T/yr	lb/hr	T/yr	lb/hr	T/yr
<b>Point Sources</b>												
<b>Pre-Project Potential to Emit</b>	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
<b>Post Project Potential to Emit</b>	0.11	0.22	0.01	0.01	0.94	0.98	0.40	0.42	4.62	20.04	0.00	0.00
<b>Changes in Potential to Emit</b>	<b>0.11</b>	<b>0.22</b>	<b>0.01</b>	<b>0.01</b>	<b>0.94</b>	<b>0.98</b>	<b>0.40</b>	<b>0.42</b>	<b>4.62</b>	<b>20.04</b>	<b>0.00</b>	<b>0.00</b>

Because of the daily coating material use limits imposed by DEQ, and agreed to by the facility in applying for this Automotive Coating "General Permit", no ELs specified in IDAPA 58.01.01.585 or 586 are expected to be exceeded by the facility (see Appendix A). In addition, because daily coating use is limited to 4.0 gal/day facility-wide HAPs emissions are inherently limited to less than 10 T/yr for any one HAP and 25 T/yr for all HAPs combined (see Appendix A).

### **Ambient Air Quality Impact Analyses**

Because of the daily coating material use limits imposed by DEQ, and agreed to by the facility in applying for this Automotive Coating "General Permit", it needs to be determined if the PTE for the automotive coating operation exceeds the DEQ modeling guideline thresholds. The following table compares the post-project facility-wide annual emissions to the DEQ modeling guideline thresholds (per the State of Idaho Air Quality Modeling Guideline, 12/31/2002).

**Table 5 PTE FOR CRITERIA POLLUTANTS COMPARED TO THE DEQ MODELING GUIDELINE THRESHOLDS**

Pollutant	PTE (T/yr) or lb/hr if listed	DEQ Modeling Guideline Thresholds (T/yr) or lb/hr if listed	Exceeds Modeling Guideline Threshold?
PM <sub>10</sub>	0.22 or 0.11 lb/hr	1 or 0.2 lb/hr	No
SO <sub>2</sub>	0.03	1	No
NO <sub>x</sub>	0.97	1	No
CO	0.42 lb/hr	14 lb/hr	No
Lead	6E-5 or 0.004 lb/mo	0.6 or 10 lb/month	No

Therefore, the installation of the new automotive coating operation does not require criteria pollutant modeling.

As presented previously in the DEQ Automotive Coatings EI Spreadsheet (see the DEQ website) there are no TAPs that required facility modeling for exceeding the pounds per hour screening levels provided in IDAPA 58.01.01.585 and .586. Therefore, the installation of a new automotive coating operation does not require TAPs modeling.

**REGULATORY ANALYSIS**

***Attainment Designation (40 CFR 81.313)***

Taylor Chevrolet Buick & Cadillac is located in Madison County, which is designated as attainment or unclassifiable for PM<sub>2.5</sub>, PM<sub>10</sub>, SO<sub>2</sub>, NO<sub>2</sub>, CO, and Ozone. Refer to 40 CFR 81.313 for additional information.

***Permit to Construct (IDAPA 58.01.01.201)***

IDAPA 58.01.01.201                      Permit to Construct Required

The PTC rules under IDAPA 58.01.01.201 require that “No owner or operator may commence construction or modification of any stationary source, facility, major facility, or major modification without first obtaining a permit to construct from the Department which satisfies the requirements of Sections 200 through 228 unless the source is exempted in any of Sections 220 through 223.” Therefore, DEQ staff analyzed the data from the permit application for the installation of this automotive coating operation to determine if it is exempt from obtaining a PTC according to Sections 220 through 223.

IDAPA 58.01.01.220                      General Exemption Criteria for Permit to Construct Exemptions

In accordance with IDAPA 58.01.01.220.01.a, the maximum capacity of the source to emit an air pollutant under its physical and operational design without consideration of limitations on emissions such as air pollution control equipment, restrictions on hours of operation and restrictions on the type and amount of material combusted, stored, or processed shall not equal or exceed 100 tons/yr for all regulated air pollutants. As previously presented in Table 2, the proposed project results in uncontrolled potential emissions of less than 100 tons/yr for all regulated air pollutants. Therefore, the project meets the criteria set forth in Section 220 and may be exempt from PTC requirements. In addition, the criteria set forth in Section 221, 222, or 223 must be met to be exempt from PTC requirements.

IDAPA 58.01.01.221                      Category I Exemption Criteria

In accordance with IDAPA 58.01.01.221.01, the maximum capacity of a source to emit an air pollutant under its physical and operational design considering limitations on emissions such as air pollution control equipment, restrictions on hours of operation and restrictions on the type and amount of material combusted, stored or processed shall be less than ten percent (10%) of the significant emission rates set out in the definition of significant at Section 006. The following table compares the post-project facility-wide annual PTE to 10% of the significance threshold listed in IDAPA 58.01.01.006.104 in order to determine if the project may qualify for a Category I exemption.

**Table 6 PTE FOR CRITERIA POLLUTANTS COMPARED TO THE SIGNIFICANCE THRESHOLDS**

Pollutant	PTE (T/yr)	10% of the Significance Threshold (T/yr)	Exceeds 10% of the Significance Threshold?
PM <sub>10</sub>	0.22	1.5	No
SO <sub>2</sub>	0.03	4.0	No
NO <sub>x</sub>	0.97	4.0	No
CO	0.42	10.0	No
VOC	20.05	4.0	Yes

The potential VOC emission rate of the proposed project is indicated in Table 6 above, which is above 10% of the significant emission rate listed in IDAPA 58.01.01.006.104. Therefore, the permitting of an existing automotive coating operation does not qualify for a Category I exemption.

***Tier II Operating Permit (IDAPA 58.01.01.401)***

IDAPA 58.01.01.401 Tier II Operating Permit

The application was submitted for a permit to construct (refer to the Permit to Construct section), and an optional Tier II operating permit has not been requested. Therefore, the procedures of IDAPA 58.01.01.400–410 were not applicable to this permitting action.

***Visible Emissions (IDAPA 58.01.01.625)***

IDAPA 58.01.01.625 Visible Emissions

The emissions from the automotive coating process are subject to the State of Idaho visible emissions standard of 20% opacity. This requirement is assured by Permit Condition 6.

***Rules for the Control of Odors (IDAPA 58.01.01.775-776)***

IDAPA 58.01.01.775-776 Rules for the Control of Odors

The facility is subject to the general restrictions for the control of odors from the facility. This requirement is assured by Permit Conditions 7 and 12.

***Title V Classification (IDAPA 58.01.01.300, 40 CFR Part 70)***

IDAPA 58.01.01.301 Requirement to Obtain Tier I Operating Permit

IDAPA 58.01.01.006.118 defines a Tier I source as “Any source located at a major facility as defined in Section 008.” IDAPA 58.01.01.008.10 defines a Major Facility as either:

- For HAPS a facility with the potential to emit ten (10) tons per year (T/yr) or more of any hazardous air pollutant, other than radionuclides, or
- The facility emits or has the potential to emit twenty-five (25) T/yr or more of any combination of any hazardous air pollutants, other than radionuclides.

Or, for non-attainment areas:

- The facility is located in a “serious” particulate matter (PM<sub>10</sub>) nonattainment area and the facility has the potential to emit seventy (70) T/yr or more of PM<sub>10</sub>, or

- The facility is located in a “serious” carbon monoxide nonattainment area in which stationary sources are significant contributors to carbon monoxide levels and the facility has the potential to emit fifty (50) T/yr or more of carbon monoxide, or
- The facility is located in an ozone transport region established pursuant to 42 U.S.C. Section 7511c and the facility has the potential to emit fifty (50) T/yr or more of volatile organic compounds, or
- The facility is located in an ozone nonattainment area and, depending upon the classification of the nonattainment area, the facility has the potential to emit the following amounts of volatile organic compounds or oxides of nitrogen; provided that oxides of nitrogen shall not be included if the facility has been identified in accordance with 42 U.S.C. Section 7411a(f)(1) or (2) if the area is “marginal” or “moderate,” one hundred (100) T/yr or more, if the area is “serious,” fifty (50) tpy or more, if the area is “severe,” twenty-five (25) T/yr or more, and if the area is “extreme,” ten (10) T/yr or more.
- The facility emits or has the potential to emit one hundred (100) T/yr or more of any regulated air pollutant. The fugitive emissions shall not be considered in determining whether the facility is major unless the facility is a “Designated Facility”:

Uncontrolled HAP emissions were calculated by using the DEQ Automotive Coating EI spreadsheet (see the DEQ website) and setting paint use to 4.0 gallons per day (as limited by the permit). Then worst-case HAP emissions were determined for all paints listed in the spreadsheet. Then emissions were assumed to occur 8,760 hours per year as a worst-case assumption.

The following table compares the post-project facility-wide annual worst-case uncontrolled emission rate for all HAPs emitted by the source to the HAPS Major Source thresholds in order to determine if the facility is a HAPs Major Source.

**Table 7 PTE FOR HAPs POLLUTANTS COMPARED TO THE HAPs MAJOR SOURCE THRESHOLDS**

HAPS Pollutants	PTE (T/yr)	Major Source Threshold (T/yr)	Exceeds the Major Source Threshold?
Ethyl benzene	0.61	10	No
Methyl Isobutyl Ketone (MIBK)	1.25	10	No
Naphthalene	2.32	10	No
Toluene	1.90	10	No
Styrene	2.49	10	No
Xylene (o-, m-, p-isomers)	2.20	10	No
<b>Total</b>	<b>10.77</b>	<b>25</b>	<b>No</b>

As presented in the preceding table the PTE for each HAP is less than 10 T/yr and the PTE for all HAPs combined is less than 25 T/yr. Therefore, this facility is not a HAPs Major Source subject to Tier I permitting requirements.

As discussed previously the facility is located in Madison County (AQCR 61), which is designated as attainment for PM<sub>2.5</sub>, PM<sub>10</sub>, SO<sub>2</sub>, NO<sub>x</sub>, CO, and Ozone for federal and state criteria air pollutants. Therefore, the following table compares the post-project facility-wide annual PTE for all criteria pollutants emitted by the source to the applicable criteria pollutant Major Source thresholds in order to determine if the facility is a criteria pollutant Major Source.



§ 63.11170

Am I subject to this subpart?

In accordance with §63.11170(a), this automotive coating operation may be subject to this subpart because the facility will be operated as an area source of HAP. The facility is a source of HAP that is not a major source of HAP, is not located at a major source, and is not part of a major source of HAP emissions. In addition, the facility will perform one or more activities listed in this section, including spray application of coatings, as defined in §63.11180, to motor vehicles and mobile equipment including operations that are located in stationary structures at fixed locations.

§ 63.11171

How do I know if my source is considered a new source or an existing source?

In accordance with §63.11171(b), the automotive coating operation is the collection of mixing rooms and equipment; spray booths, curing ovens, and associated equipment; spray guns and associated equipment; spray gun cleaning equipment; and equipment used for storage, handling, recovery, or recycling of cleaning solvent or waste paint. Paint stripping was not proposed as a business activity.

In accordance with §63.11171(c), this automotive coating operation is an existing source because it commenced construction prior to September 17, 2007, by installing new paint stripping or surface coating equipment, and the new surface coating equipment will be used at a source that was actively engaged in paint stripping and/or miscellaneous surface coating prior to September 17, 2007.

§ 63.11172

When do I have to comply with this subpart?

In accordance with §63.11172(a)(2), because the initial startup of the facility occurred prior to January 9, 2008, the compliance date is January 10, 2011.

§ 63.11173

What are my general requirements for complying with this subpart?

Because the facility has not proposed paint-stripping activities, the requirements of §63.11173(a) through (f) are not applicable. Because the facility is an automotive coating operation, in accordance with §63.11173(e), the permittee must meet the requirements of in paragraphs (e)(1) through (e)(5) of this section.

In accordance with §63.11173(f), each owner or operator of an affected automotive coating operation must ensure and certify that all new and existing personnel, including contract personnel, who spray apply surface coatings, as defined in §63.11180, are trained in the proper application of surface coatings as required by paragraph (e)(1) of this section. The training program must include, at a minimum, the items listed in paragraphs (f)(1) through (f)(3) of this section.

In accordance with §63.11173(g), as required by paragraph (e)(1) of this section, all new and existing personnel at an affected motor vehicle and mobile equipment or miscellaneous surface coating source, including contract personnel, who spray apply surface coatings, as defined in §63.11180, must be trained by the dates specified in paragraphs (g)(1) and (2) of this section. Employees who transfer within a company to a position as a painter are subject to the same requirements as a new hire.

Compliance with these requirements is assured by permit condition 18.

§ 63.11174

What parts of the General Provisions apply to me?

In accordance with §63.11174(a), Table 1 of this subpart shows which parts of the General Provisions in subpart A apply. Compliance with these requirements is assured by permit condition 17.

In accordance with §63.11174(b), an owner or operator of an area source subject to this subpart is exempt from the obligation to obtain a permit under 40 CFR part 70 or 71 provided that a permit under 40 CFR 70.3(a) or 71.3(a) is not required for a reason other than becoming area source subject to this subpart. This permit application and permitting action involve a Permit to Construct, and will not utilize the requirements and procedures in IDAPA 58.01.01.300-399 for the issuance of Tier I operating permits.

§ 63.11175

What notifications must I submit?

In accordance with §63.11175(a), because the facility is a surface coating operation subject to this subpart, the initial notification required by §63.9(b) must be submitted. For this existing operation, the Initial Notification must be submitted no later than on or before March 11, 2011.

In accordance with §63.11175(b), because the facility is an existing source, the permittee is not required to submit a separate notification of compliance status in addition to the initial notification specified in paragraph (a) of this subpart provided the permittee was able to certify compliance on the date of the initial notification, as part of the initial notification, and the permittee's compliance status has not since changed. The permittee must submit a Notification of Compliance Status on or before March 11, 2011. The permittee is required to submit the information specified in paragraphs (b)(1) through (4) of this section with the Notification of Compliance Status.

Compliance with these requirements is assured by permit condition 19.

§ 63.11176 What reports must I submit?

In accordance with §63.11176(a), because the permittee is an owner or operator of a paint stripping, motor vehicle or mobile equipment, or miscellaneous surface coating affected source, the permittee is required to submit a report in each calendar year in which information previously submitted in either the initial notification required by §63.11175(a), Notification of Compliance, or a previous annual notification of changes report submitted under this paragraph, has changed. Deviations from the relevant requirements in §63.11173(a) through (d) or §63.11173(e) through (g) on the date of the report will be deemed to be a change. The annual notification of changes report must be submitted prior to March 1 of each calendar year when reportable changes have occurred and must include the information specified in paragraphs (a)(1) through (2) of this section.

Compliance with these requirements is assured by permit condition 20.

Because the facility has not proposed to conduct paint stripping operations, the MeCl minimization plan requirements are not applicable (see permit condition 9).

§ 63.11177 What records must I keep?

In accordance with §63.11177, because the permittee is the owner or operator of a surface coating operation, the permittee must keep the records specified in paragraphs (a) through (d) and (g) of this section. Because the permittee has not proposed to conduct paint stripping operations, the requirements of paragraphs (e) and (f) of this section are not applicable. Compliance with these requirements is assured by permit condition 18.

§ 63.11178 In what form and for how long must I keep my records?

In accordance with 40 CFR 63.11178(a) because the permittee is the owner or operator of an affected source, the permittee must maintain copies of the records specified in §63.11177 for a period of at least five years after the date of each record. Copies of records must be kept on site and in a printed or electronic form that is readily accessible for inspection for at least the first two years after their date, and may be kept off-site after that two year period. Compliance with these requirements is assured by permit condition 18.

§ 63.11179 Who implements and enforces this subpart?

In accordance with §63.11179(a), this subpart can be implemented and enforced by the U.S. Environmental Protection Agency (EPA), or a delegated authority. At the time of this permitting action, the EPA has not delegated authority to the State of Idaho. However, IDAPA 58.01.01.107.03.i incorporates by reference all Federal Clean Air Act requirements including 40 CFR 63, Subpart HHHHHH. Therefore, the requirements of this subpart have been placed in the permit.

§ 63.11180 What definitions do I need to know?

Terms used in this subpart are defined in accordance with §63.11180.

### **Permit Conditions Review**

This section describes the permit conditions for this initial permit.

Permit condition 1 establishes the permit to construct scope.

Permit condition 2 provides a description of the purpose of the permit and the regulated sources, the process, and the control devices used at the facility.

Permit condition 3 provides a process description of the facility.

Permit condition 4 provides a description of the control devices used at the facility.

Permit condition 5 establishes hourly and annual emissions limits for PM<sub>10</sub> and VOC emissions from the automotive coating operation.

As mentioned previously, Permit Condition 6 establishes a 20% opacity limit for the paint booth stacks, vents, or functionally equivalent openings associated with the automotive coating operation.

As mentioned previously, Permit Condition 7 establishes that the permittee shall not allow, suffer, cause, or permit the emission of odorous gasses, liquids, or solids to the atmosphere in such quantities as to cause air pollution.

Permit Condition 8 establishes that only natural gas or LPG is allowed to be used as fuel in the paint booth heater as proposed by the applicant.

Permit condition 9 establishes that the facility will not use MeCl to remove paint from vehicles at the facility. This was done because MeCl was not proposed to be used at this facility by the Applicant and the emissions were not included in the DEQ Automotive Coating EI Spreadsheet (see the DEQ website). In addition, Subpart HHHHHH has additional requirements for facilities that use MeCl to remove paint as mentioned previously in the discussion of Subpart HHHHHH in the MACT Applicability Section.

Permit condition 10 establishes a daily use limit for all coating materials used in the automotive coating process as proposed by the Applicant. This limit was established because it was the easiest way for the Applicant to demonstrate compliance with the PM<sub>10</sub> and VOC emissions limit specified in permit condition 5 and the TAPs emissions limits specified in the DEQ Automotive Coating EI Spreadsheet (see the DEQ website).

Permit Condition 11 excludes bed liner component B coatings from each daily usage total. For those bed liner coatings analyzed, component B coatings did not contain substances which would result in emissions of regulated TAP. Component A coatings (also referred to as the "iso" component) are counted toward the daily usage limit in Permit Condition 10 because these coatings contain isocyanates (including HDI and/or MDI) which result in the emissions of regulated TAP.

Permit condition 12 establishes that the permittee conduct all automotive coating operations in the paint booth or preparation station with the filters in place, exhaust fan(s) operating, and door(s) or curtain(s) closed, that the operation shall use a HVLP spray gun, and that the permittee shall maintain and operate the paint booth and preparation station exhaust filter system in accordance with the manufacturer's specifications. This condition also defines what a booth and preparation station used for applying coating is.

Permit condition 13 establishes that the permittee shall maintain records of all odor complaints received, perform appropriate corrective actions, and maintain records of corrective actions taken at the facility for the automotive coating process. This was required because automotive operation operations are expected to have odors that might be offensive to their immediate neighbors.

Permit condition 14 establishes that the permittee shall maintain material purchase records and Material Safety Data Sheets (MSDS) for the automotive coating process. This condition was placed in the permit to ensure compliance with the Coating Materials Use Limit Permit Condition.

Permit Condition 15 establishes that the permittee shall maintain daily usage records of pre-treatment wash primers, primers, topcoats, clear coats, thinners/reducers, and bed liner components containing isocyanates materials used in the automotive coating process. This condition was placed in the permit to ensure compliance with the Coating Materials Use Limit permit condition.

Permit condition 16 establishes that the permittee shall maintain records as required by the General Provision recordkeeping requirements.

Permit condition 17 establishes parameters that will allow the facility to comply with the general operating requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 18 establishes parameters that will allow the facility to comply with the monitoring and recordkeeping requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 19 establishes parameters that will allow the facility to comply with the initial notification and reporting requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 20 establishes parameters that will allow the facility to comply with the annual notification and reporting requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 21 establishes that the federal requirements of 40 CFR Part 63 are incorporated by reference into the requirements of this permit per current DEQ guidance.

## **PUBLIC REVIEW**

### ***Public Comment Opportunity***

An opportunity for public comment period on the application was provided in accordance with IDAPA 58.01.01.209.01.c or IDAPA 58.01.01.404.01.c. During this time, there were no comments on the application and there was not a request for a public comment period on DEQ's proposed action. Refer to the chronology for public comment opportunity dates.

## APPENDIX A – EMISSIONS INVENTORIES

### Coating Operation Emissions Calculations:

A daily coatings material use limit needs to be established for Automotive Coating operations that demonstrates compliance with State Law. Specifically, compliance with IDAPA 58.01.01.585 and .586 for toxic air pollutants (TAPs) needs to be determined. Therefore, DEQ staff created the DEQ Automotive Coating EI spreadsheet (see the DEQ website). This spreadsheet contains paints from two different manufacturers of paints used in the automotive coating industry and multiple paint systems for each brand. The paint brands chosen were based upon discussions with a national paint distributor with several stores throughout the state of Idaho. The TAPs data entered in the spreadsheet was taken from the MSDSs for the paints listed. Included in the calculations was a safety factor of 19% since all paints available were not analyzed. With this safety factor it is reasonably presumed that the data represents all available automotive coatings. The spreadsheet was then used to demonstrate that with 4.0 gallons per day of coating use, the ELs listed in IDAPA 58.01.01.585 and .586 would not be exceeded for any of the coatings listed in the spreadsheet. The 4.0 gallons per day of coating was then used to determine worst-case PM<sub>10</sub> and VOC emissions from Automotive Coating operations.

Spray booth emissions of methylene diisocyanate (MDI) resulting from the application of the “iso” component coating during bed lining coating operations were estimated using the equation and assumptions from Section 19.0 of the MDI/Polymeric MDI Emissions Reporting Guidelines for the Polyurethane Industry.<sup>1</sup> In this equation it was assumed that 100% of the “iso” component sprayed was MDI ( $k_{MDI} = 1.0$ ), that the combined spray and dry time to apply up to 4 gallons of MDI-based “iso” component was 4 hours or less per day, that “iso” spray coatings were applied 365 days per year, and that “iso” spray coatings were applied at less than 95°F. Although spray booth filtration is required, no additional removal or reduction of MDI emissions was assumed (0% control efficiency).

Uncontrolled annual emissions were estimated by scaling up the coating operation from the 2,080 hrs/yr (8 hr/day x 260 day/yr, normal business hours) to 8,760 hr/yr (24 hr/day x 365 day/yr). Therefore the scaling factor = 8,760 hr/yr ÷ 2,080 hr/yr = 4.2.

Detailed emissions estimates from the spreadsheet are provided in the following pages.

### Paint Booth Heater Emissions Calculations:

To determine worst-case emissions from the paint booth(s) heater(s) the maximum heat input rating of the burner was assumed to be 10 MMBtu/hr with operation of 2,080 hr/yr.

Uncontrolled annual emissions were again estimated by scaling up the operation of the burner from the 2,080 hr/yr (8 hr/day x 260 day/yr, normal business hours) to 8,760 hr/yr (24 hr/day x 365 day/yr).

Therefore the scaling factor = 8,760 hr/yr ÷ 2,080 hr/yr = 4.2.

Detailed emissions estimates from the spreadsheet are provided in the following pages.

---

<sup>1</sup> MDI/Polymeric MDI Emissions Reporting Guidelines for the Polyurethane Industry, Alliance for the Polyurethanes Industry (API), 2004.

**Coating: Bed Liner Components**

Content Weight %	Density	Solids (particulate)	Hexamethylene Diisocyanate (HDI)(HAP)	Methylene Diisocyanate (MDI)(HAP)
BASF XS-310				
Vortex				39.00%
Rhino 2170 A			0.10%	60.00%
Monstalliner			0.35%	
Morton 999623				9.66%
Speedliner 1000				11.09%
Speedliner Primer 450 & 460				15.00%
Langeman 700 A				
Content				
lb/gal				

Coating Material	Density	Solids (particulate)	Hexamethylene Diisocyanate (HDI)(HAP)	Methylene Diisocyanate (MDI)(HAP)
BASF XS-310	9.80	0.00	0.00	3.82
Vortex	8.12	0.00	0.00	4.87
Rhino 2170 A	10.33	0.00	0.00	6.20
Monstalliner	9.77	0.00	0.01	0.00
Morton 999623	9.98	0.00	0.03	0.00
Speedliner 1000	8.33	0.00	0.00	0.80
Speedliner Primer	8.33	0.00	0.00	0.92
Langeman 700 A	9.10	0.00	0.00	1.37
Maximum (lb/gal)	10.33	0.00	0.03	6.20

Emission Rate (lb/hr) **0.0E+00** **1.0E-03** see "Isoc" MDI sheet

IDAPA TAP EL **2.0E-03**

Below EL7 Yes

Daily Use Rates Averaging Period (gal/day)	Transfer Efficiency (%)
4.00	24
	65.00%

Isocyanate Reaction Factor (ratio)	Annual Usage Rate (gal/yr)	Safety Factor (ratio)
85.00%	1,460.0	1.20

### Coating: Bed Liner "Iso" Component (MDI-Based)

$$L_{sp} = (V_{air}^{359}) * (273.15/T_{sp}) * 60 * (C_{MDI}/1000000) * MW * k_{MDI} * t_{sp}$$

where:

$L_{sp}$  = the annual emissions for spray coating operations

$V_{air}$  = the exhaust airflow rate

359 = the molar volume of an ideal gas

$T_{sp}$  = the spray temperature

$C_{MDI}$  =  $(VP_{MDI}/760) * 10^6$  = the MDI concentration in the exhaust air

$VP_{MDI}$  = MDI vapor pressure at exhaust temperature

MW = the molecular weight of MDI (250.26)

$k_{MDI}$  = the adjustment factor to the vapor pressure that is a function of MDI concentration

$t_{sp}$  = hr/day x 365 day/yr = is the total time in hours/year that spray coating is occurring

$t_{hr}$  = is the total time in hours/day that spray coating is occurring

T = the spray temperature

24.77	lb/yr <sup>1</sup>
10,000	ft <sup>3</sup> /min
359	ft <sup>3</sup> /lbmol @ 0°C and 1-atm
308.15	K
0.0458	ppmv
3.48E-05	mmHg <sup>2</sup>
250.26	lb/lbmol
1.00	
1460	hr/yr
4	hr/day
95	°F

Emission Rate (lb/hr, 24-hr average)

2.83E-03

IDAPA TAP EL  
(lb/hr)

3.00E-03

Below EL?

Yes

### Coating: Bed Liner Components

Content Weight %	Coating Material	Density	Solids (particulate)	HAP <sub>tot</sub>	HAP <sub>max</sub>	Diethyl toluene diamine (DETA)	Dipropylene Glycol Methyl Ether	Polyether Polyols
	BASF XS-350 Resin					25.00%		70.00%
	Rhino 2170 B	8.83	0.00	0.00	0.00	5.00%	60.00%	
	Rhino Duraspray B	8.66	0.00	0.00	0.00	20.00%		80.00%
	Langeman Reflex Colorant	8.58	0.00	0.00	0.00	20.00%		80.00%
	Langeman Reflex 700 B	8.58	0.00	0.00	0.00			100.00%
	Langeman Reflex 700RA	8.41	0.00	0.00	0.00			
	Content lb/gal							
	BASF XS-350 Res	8.39	0.00	0.00	0.00	2.10	0.00	5.87
	Rhino 2170 B	8.83	0.00	0.00	0.00	0.44	5.30	0.00
	Rhino Duraspray B	8.66	0.00	0.00	0.00	0.00	0.00	0.00
	Langeman Reflex (	8.58	0.00	0.00	0.00	1.72	0.00	6.86
	Langeman 700 B	8.58	0.00	0.00	0.00	1.72	0.00	6.86
	Langeman Reflex :	8.41	0.00	0.00	0.00	0.00	0.00	8.41
	Maximum (lb/gal)	9.77	0.00	0.00	0.00	2.10	5.30	8.41
	Emission Rate (lb/hr)		0.0E+00	0.0E+00	0.0E+00	4.2E-01	1.1E+00	1.7E+00

IDAPA TAP EL

(lb/hr)

Below EL?

Daily Use Rates (gal/day)	Averaging Period (hr/day)	Transfer Efficiency (%)	Filter Control Efficiency (%)
4.00	24	65.00%	98.00%

Isocyanate Reaction Factor (ratio)	Annual Usage Rate (gal/yr)	Safety Factor (ratio)
85.00%	1,460.0	1.20

**General PTC**

**Automotive Coating**

**Emission Inventory - spray booth heater emissions for natural gas combustion, AP-42 Section 1.4 (7/98)**

Heat Input Capacity:  
10.00 MMBtu/hr

Operating Assumptions:  
24 hr/day  
2,080 hr/yr  
1,020 MMBtu/MMscf

Fuel Use:  
9.80E-03 MMscf/hr  
0.235 MMscf/day  
20.39 MMscf/yr

Criteria Air Pollutants	Emission Factor lb/MMscf	Emissions		Modeling Threshold		Below Threshold?	Modeling Threshold		Below Threshold?
		lb/hr	T/yr	2002 Guidance	Case-by-Case				
NO <sub>2</sub>	94	9.22E-01	9.58E-01	1	T/yr	Yes	7	T/yr	Yes
CO	40	3.92E-01	4.08E-01	14	lb/hr	Yes	70	lb/hr	Yes
PM <sub>10</sub>	7.6	7.45E-02	7.75E-02	0.2	lb/hr	Yes	0.9	lb/hr	Yes
				1	T/yr	Yes	7	T/yr	Yes
SO <sub>x</sub>	0.6	5.88E-03	6.12E-03	0.2	lb/hr	Yes	0.9	lb/hr	Yes
				1	T/yr	Yes	7	T/yr	Yes
VOC	5.5	5.39E-02	5.61E-02	40	T/yr	Yes			
			5.10E-06	0.6	T/yr	Yes			
Lead	0.0005	4.90E-06	lb/mo						
			3.65E-03	10	lb/mo	Yes			

Note: 100 lb/mo Pb in guidance reduced by factor of 10 based on latest Pb NAAQS (reduced in 2008 from 1.5 ug/m3 to 0.15 ug/m3)

Hazardous Air Pollutants (HAP) and Toxic Air Pollutants (TAP)	lb/MMscf	lb/hr	T/yr	Modeling Threshold	Below Threshold?
				EL (lb/hr)	
<b>Organic HAP PAH</b>					
2-Methylnaphthalene	2.40E-05	5.59E-08	5.81E-08	9.10E-05	Yes
3-Methylchloranthrene	1.80E-06	4.19E-09	4.36E-09	2.50E-06	Yes
Acenaphthene	1.80E-06	4.19E-09	4.36E-09	9.10E-05	Yes
Acenaphthylene	1.80E-06	4.19E-09	4.36E-09	9.10E-05	Yes
Anthracene	2.40E-06	5.59E-09	5.81E-09	9.10E-05	Yes
Benzo(a)anthracene	1.80E-06	4.19E-09	4.36E-09	9.10E-05	See POM
Benzo(a)pyrene	1.20E-06	2.79E-09	2.91E-09	2.00E-06	See POM
Benzo(b)fluoranthene	1.80E-06	4.19E-09	4.36E-09		See POM
Benzo(g,h,i)perylene	1.20E-06	2.79E-09	2.91E-09	9.10E-05	Yes
Benzo(k)fluoranthene	1.80E-06	4.19E-09	4.36E-09		See POM
Chrysene	1.80E-06	4.19E-09	4.36E-09		See POM
Dibenzo(a,h)anthracene	1.20E-06	2.79E-09	2.91E-09		See POM
Dichlorobenzene	1.20E-03	2.79E-06	2.91E-06	9.10E-05	Yes
Fluoranthene	3.00E-06	6.98E-09	7.26E-09	9.10E-05	Yes
Fluorene	2.80E-06	6.52E-09	6.78E-09	9.10E-05	Yes
Indeno(1,2,3-cd)pyrene	1.80E-06	4.19E-09	4.36E-09		See POM
Naphthalene	6.10E-04	1.42E-06	1.48E-06	3.33	Yes
Naphthalene	6.10E-04	1.42E-06	1.48E-06	9.10E-05	Yes
Phenanthrene	1.70E-05	3.96E-08	4.12E-08	9.10E-05	Yes
Pyrene	5.00E-06	1.16E-08	1.21E-08	9.10E-05	Yes
Polycyclic Organic Matter (POM, 7-PAH Group)		2.65E-08	2.76E-08	2.00E-06	Yes
<b>Organic HAP Non-PAH</b>					
Benzene	2.10E-03	4.89E-06	5.08E-06	8.00E-04	Yes
Formaldehyde	7.50E-02	1.75E-04	4.15E-05	5.10E-04	Yes
Hexane	1.80E+00	1.76E-02	4.19E-03	12	Yes
Toluene	3.40E-03	3.33E-05	7.91E-06	25	Yes
<b>Organic Non-HAP</b>					
7,12-Dimethylbenz(a)anthracene	1.60E-05	1.57E-07	3.72E-08		
Butane	2.10E+00	2.06E-02	4.89E-03		
Ethane	3.10E+00	3.04E-02	7.22E-03		
Pentane	2.60E+00	2.55E-02	6.05E-03	118	Yes
Propane	1.60E+00	1.57E-02	3.72E-03		
<b>Metal HAP</b>					
Arsenic	2.00E-04	4.66E-07	1.11E-07	1.50E-06	Yes
Barium	4.40E-03	4.31E-05	1.02E-05	0.033	Yes
Beryllium	1.20E-05	2.79E-08	6.63E-09	2.80E-05	Yes
Cadmium	1.10E-03	2.56E-06	6.08E-07	3.70E-06	Yes
Chromium	1.40E-03	1.37E-05	3.26E-06	0.033	Yes
Cobalt	8.40E-05	8.24E-07	1.96E-07	0.0033	Yes
Copper	8.50E-04	8.33E-06	1.98E-06	0.013	Yes
Manganese	3.80E-04	3.73E-06	8.85E-07	0.067	Yes
Mercury	2.60E-04	2.55E-06	6.05E-07	0.003	Yes
Molybdenum	1.10E-03	1.08E-05	2.56E-06	0.333	Yes
Nickel	2.10E-03	4.89E-06	1.16E-06	2.70E-05	Yes
Selenium	2.40E-05	2.35E-07	5.59E-08	0.013	Yes
Vanadium	2.30E-03	2.25E-05	5.35E-06	0.003	Yes
Zinc	2.90E-02	2.84E-04	6.75E-05	0.667	Yes

NOTE: TAP emissions are based on 24-hour averages unless shown in bold, which are based on annual averages.

**General PTC  
Automotive Coating**

**Emission Inventory - maximum TAP/HAP results of all coatings analyzed and including booth heater emissions**

Criteria Air Pollutants	Booth Emissions	Heater Emissions	Combined Emissions	Combined Emissions	Modeling Threshold	Below Threshold?	Modeling Threshold	Below Threshold?
	lb/hr	lb/hr	lb/hr	T/yr				
					<b>2002 Guidance</b>			
NO <sub>2</sub>	0.00	0.93	0.93	0.97	1 T/yr	Yes	7 T/yr	Yes
CO	0.00	0.40	0.40	0.42	14 lb/hr	Yes	70 lb/hr	Yes
PM <sub>10</sub>	0.03	0.08	0.11	0.22	0.2 lb/hr	Yes	0.9 lb/hr	Yes
					1 T/yr	Yes	7 T/yr	Yes
SO <sub>x</sub>	0.000	0.006	0.006	0.03	0.2 lb/hr	Yes	0.9 lb/hr	Yes
					1 T/yr	Yes	7 T/yr	Yes
VOC	4.56	0.06	4.62	20.04	40 T/yr	Yes		
	0.E+00	5.E-06	5.E-06	6.E-06	0.6 T/yr	Yes		
Lead	lb/mo	lb/mo	lb/mo					
	0.000	0.004	0.004		10 lb/mo	Yes		

Note: 100 lb/mo Pb in guidance reduced by factor of 10 based on latest Pb NAAQS (reduced in 2008 from 1.5 ug/m<sup>3</sup> to 0.15 ug/m<sup>3</sup>)

Hazardous Air Pollutants (HAP) and Toxic Air Pollutants (TAP)	Booth Emissions	Heater Emissions	Combined Emissions	Combined Emissions	Modeling Threshold	Below Threshold?
	lb/hr	lb/hr	lb/hr	T/yr	EL (lb/hr)	
<b>Organic HAP PAH</b>						
2-Methylnaphthalene	0.00E+00	5.59E-08	5.59E-08	5.81E-08	9.10E-05	Yes
3-Methylchloranthrene	0.00E+00	4.19E-09	4.19E-09	4.36E-09	2.50E-06	Yes
Acenaphthene	0.00E+00	4.19E-09	4.19E-09	4.36E-09	9.10E-05	Yes
Acenaphthylene	0.00E+00	4.19E-09	4.19E-09	4.36E-09	9.10E-05	Yes
Anthracene	0.00E+00	5.59E-09	5.59E-09	5.81E-09	9.10E-05	Yes
Benzo(a)anthracene	0.00E+00	4.19E-09	4.19E-09	4.36E-09	9.10E-05	See POM
Benzo(a)pyrene	0.00E+00	2.79E-09	2.79E-09	2.91E-09	2.00E-06	See POM
Benzo(b)fluoranthene	0.00E+00	4.19E-09	4.19E-09	4.36E-09		See POM
Benzo(g,h,i)perylene	0.00E+00	2.79E-09	2.79E-09	2.91E-09	9.10E-05	Yes
Benzo(k)fluoranthene	0.00E+00	4.19E-09	4.19E-09	4.36E-09		See POM
Chrysene	0.00E+00	4.19E-09	4.19E-09	4.36E-09		See POM
Dibenzo(a,h)anthracene	0.00E+00	2.79E-09	2.79E-09	2.91E-09		See POM
Dichlorobenzene	0.00E+00	2.79E-06	2.79E-06	2.91E-06	9.10E-05	Yes
7,12-Dimethylbenz(a)anthracene	0.00E+00	1.57E-07	1.57E-07	1.63E-07	9.10E-05	Yes
Fluoranthene	0.00E+00	6.98E-09	6.98E-09	7.26E-09	9.10E-05	Yes
Fluorene	0.00E+00	6.52E-09	6.52E-09	6.78E-09	9.10E-05	Yes
Indeno(1,2,3-cd)pyrene	0.00E+00	4.19E-09	4.19E-09	4.36E-09		See POM
Phenanthrene	0.00E+00	3.96E-08	3.96E-08	4.12E-08	9.10E-05	Yes
Pyrene	0.00E+00	1.16E-08	1.16E-08	1.21E-08	9.10E-05	Yes
Polycyclic Organic Matter (POM, 7-F)	0.00E+00	2.65E-08	2.65E-08	2.76E-08	2.00E-06	Yes
<b>Organic HAP Non-PAH</b>						
Benzene	0.00E+00	4.89E-06	4.89E-06	5.08E-06	8.00E-04	Yes
Ethyl Benzene	1.40E-01	0.00E+00	1.40E-01	6.14E-01	2.90E+01	Yes
Hexamethylene Diisocyanate (HDI)	2.00E-03	0.00E+00	2.00E-03	8.74E-03	2.00E-03	Yes
n-Hexane	2.51E-02	1.76E-02	4.28E-02	1.28E-01	1.20E+01	Yes
Methyl Ethyl Ketone (MEK)	2.76E-01	0.00E+00	2.76E-01	1.21E+00	3.93E+01	Yes
Methyl Isobutyl Ketone (MIBK)	2.87E-01	0.00E+00	2.87E-01	1.26E+00	1.37E+01	Yes
Methylene Diisocyanate (MDI)	2.83E-03	0.00E+00	2.83E-03	1.24E-02	3.00E-03	Yes
Styrene	5.73E-01	0.00E+00	5.73E-01	2.51E+00	6.67E+00	Yes
Toluene	4.38E-01	3.33E-05	4.38E-01	1.92E+00	2.50E+01	Yes
Xylene	5.07E-01	0.00E+00	5.07E-01	2.22E+00	2.90E+01	Yes
<b>Organic Non-HAP</b>						
Acetone	1.56E+00	0.00E+00	1.56E+00	6.83E+00	1.19E+02	Yes
Butyl Acetate	1.19E+00	0.00E+00	1.19E+00	5.21E+00	4.73E+01	Yes
n-Butyl Alcohol	1.10E+00	0.00E+00	1.10E+00	4.81E+00	1.00E+01	Yes
Carbon Black	8.33E-04	0.00E+00	8.33E-04	3.65E-03	2.30E-01	Yes
Cyclohexane	1.29E-02	0.00E+00	1.29E-02	5.64E-02	7.00E+01	Yes
Diisobutyl Ketone	8.30E-02	0.00E+00	8.30E-02	3.64E-01	9.67E+00	Yes
Ethyl Acetate	2.45E-01	0.00E+00	2.45E-01	1.07E+00	9.33E+01	Yes
Ethyl Alcohol	1.90E-02	0.00E+00	1.90E-02	8.34E-02	1.25E+02	Yes
Formaldehyde	0.00E+00	1.75E-04	1.75E-04	1.82E-04	5.10E-04	Yes
Heptane	2.09E-02	0.00E+00	2.09E-02	9.17E-02	1.09E+02	Yes
Isobutanol	3.55E-01	3.33E-05	3.55E-01	1.56E+00	1.00E+01	Yes
Isobutyl Acetate	1.10E-02	0.00E+00	1.10E-02	4.82E-02	4.67E+01	Yes
Isophorone Diisocyanate Polymer	2.50E-03	1.57E-07	2.50E-03	1.10E-02	6.00E-03	Yes
Isopropyl Alcohol (IPA)	6.63E-01	2.06E-02	6.84E-01	2.93E+00	6.53E+01	Yes
Kaolin	3.93E-03	3.04E-02	3.43E-02	4.88E-02	1.33E-01	Yes
1-Methoxy-2-Propanol Acetate	3.21E-01	2.55E-02	3.46E-01	1.43E+00	2.40E+01	Yes
Methyl Acetate	3.32E-01	1.57E-02	3.48E-01	1.47E+00	4.07E+01	Yes
Methyl Amyl Ketone	1.43E+00	0.00E+00	1.43E+00	6.25E+00	1.57E+01	Yes
Methyl Isoamyl Ketone	7.85E-02	4.31E-05	7.85E-02	3.44E-01	1.60E+01	Yes
Methyl Propyl Ketone	1.58E-01	2.56E-06	1.58E-01	6.90E-01	4.67E+01	Yes
Mica	1.09E-04	8.24E-07	1.10E-04	4.80E-04	2.00E-01	Yes
Naphthalene	5.34E-01	1.42E-06	5.34E-01	2.34E+00	3.33E+00	Yes
Pentane	0.00E+00	2.55E-02	2.55E-02	2.65E-02	1.18E+02	Yes
Propionic Acid	1.51E-02	2.55E-06	1.51E-02	6.61E-02	2.00E+00	Yes
Silica Amorphous	1.67E-03	1.08E-05	1.68E-03	7.31E-03	6.67E-01	Yes
Silica Gel	1.12E-03	4.89E-06	1.13E-03	4.92E-03	6.67E-01	Yes
Silica Silicon Dioxide	2.35E-03	2.35E-07	2.35E-03	1.03E-02	6.70E-03	Yes
Stoddard Solvent Mineral Spirits	6.74E-01	2.25E-05	6.74E-01	2.95E+00	3.50E+01	Yes
1,2,4 Trimethyl Benzene	1.88E-01	0.00E+00	1.88E-01	8.24E-01	8.20E+00	Yes
VM&P Naphtha	2.20E-01	0.00E+00	2.20E-01	9.63E-01	9.13E+01	Yes
<b>Metal HAP</b>						
Antimony	1.86E-03	0.00E+00	1.86E-03	8.17E-03	3.30E-02	Yes
Arsenic	0.00E+00	4.66E-07	4.66E-07	4.84E-07	1.50E-06	Yes
Beryllium	0.00E+00	2.79E-08	2.79E-08	2.91E-08	2.80E-05	Yes
Cadmium	0.00E+00	2.56E-06	2.56E-06	2.66E-06	3.70E-06	Yes
Chromium III	5.63E-04	1.37E-05	5.77E-04	2.48E-03	3.30E-02	Yes
Cobalt	0.00E+00	8.24E-07	8.24E-07	8.56E-07	3.30E-03	Yes
Copper	0.00E+00	8.33E-06	8.33E-06	8.67E-06	1.30E-02	Yes
Manganese	0.00E+00	3.73E-06	3.73E-06	3.87E-06	6.70E-02	Yes
Mercury	0.00E+00	2.55E-06	2.55E-06	2.65E-06	3.00E-03	Yes
Molybdenum	0.00E+00	1.08E-05	1.08E-05	1.12E-05	3.33E-01	Yes
Nickel	0.00E+00	4.89E-06	4.89E-06	5.08E-06	2.70E-05	Yes
Selenium	0.00E+00	2.35E-07	2.35E-07	2.45E-07	1.30E-02	Yes
Vanadium	0.00E+00	2.25E-05	2.25E-05	2.35E-05	3.00E-03	Yes
Zinc	0.00E+00	2.84E-04	2.84E-04	2.96E-04	6.67E-01	Yes
<b>Metal Non-HAP</b>						
Aluminum	4.66E-01	0.00E+00	4.66E-01	2.04E+00	6.67E-01	Yes
Barium	2.60E-04	4.31E-05	3.03E-04	1.18E-03	3.30E-02	Yes
		HAP <sub>TOT</sub>	2.28	9.99		
		HAP <sub>MAX</sub>	0.58	2.55		

**Assumptions when estimating spray booth heater emissions:**

- Maximum heater size 10.00 MMBtu/hr
- Annual heater operation 2,080 hr/yr
- Fuel limited to natural gas only

**Assumptions when estimating spray booth emissions:**

- Maximum coating use rate: 4.00 gal/day for all coatings (excluding "B" component) hr/day average
- Averaging period 24 hr/day average
- Annual booth operation 8,760 hr/yr
- Safety factor 1.20 allowance for coatings not analyzed
- Transfer efficiency 65% control for particulates
- Filter removal efficiency 98% control for particulates
- Isocyanate reaction factor 85% control for isocyanates
- Maximum coating density 16.76 lb/gal
- % of monomer in mixture 1% for diisocyanates in hardener mixture
- If no % of TAP was listed in the MSDS, then 1.0% was assumed

**Assumptions when estimating spray booth MDI emissions from truck bed lining:**

- Spray booth emissions were estimated referencing the equation and assumptions from Section 19.0 of the MDI/Polymeric MDI Emissions Reporting Guidelines for the Polyurethane Industry, Alliance for the Polyurethanes Industry (API), 2004.
- 100% of isocyanate content was MDI (k<sub>MDI</sub> = 1.0).
- Spray booth filtration does not reduce or remove MDI (0% control efficiency).
- The combined spray and dry time to apply 4 gal of "iso" component is 4 hr or less.
- Spray coatings are applied 365 days per year.
- Spray coatings are applied at less than 95°F.

**Assumptions when estimating additional VOC emissions from truck bed liner "B" component (VOC from the "iso" component were accounted for within the analysis for the 4 gal/day limit):**

- Maximum "B" use rate 4.00 gal/day (1:1 by volume A:B mixture)
- Safety factor 1.20 allowance for coatings not analyzed
- Maximum coating density 8.83 lb/gal (from "Bed Liner B" sheet)
- Averaging period 24 hr/day average
- VOC emissions 1.77 lb/hr
- B component does not contain HAP or TAP substances